


Premium 960H Realtime DVR CK3316

Supporting RS485 Over Coax



Mobile Viewer for Various OS (iPad, iPhone, Android)

RS485 Over Coax (PTZ, Camera menu control)

Practical Multi Spot (Multi Channel Sequence Programmable)

Relay Alarm Out Port (Dry Contact Type) with Master Alarm

CK3316 Series 960H Digital Video Recorder

SPECIFICATION

MODEL	CK3304	CK3308	CK3316
Operating System	Embedded Linux		
OS Firmware	Linux OS in Flash Memory		
Signal Format	NTSC or PAL (Auto / Manual)		
Memory	1GB DDR3 Memory		
Video Input	4 (BNC)	8 (BNC)	16 (BNC)
Video Output	Composite: 1		
VGA	1 Port (Max. 1920 x 1080)		
HDMI	1 Port (Max. 1920 x 1080)		
Loop Out	4	8	16
Multi Spot Output	Composite: 1		
Max. Recording Rate at 960H (FPS)	120 (NTSC) / 100 (PAL)	240 (NTSC) / 200 (PAL)	480 (NTSC) / 400 (PAL)
Audio Input / Output	4 Input / 1 Output	8 Input / 1 Output	16 Input / 1 Output
Alarm Input	4 Input	8 Input	16 Input
Master Alarm	1		
Alarm Output	4 (TTL) / 2 (Relay)	8 (TTL) / 2 (Relay)	16 (TTL) / 2 (Relay)
USB 2.0	4 x USB (2 x Front Panel, 2 x Rear Panel)		
Ethernet	10 / 100 / 1000 Mbps Ethernet (RJ-45)		
User Interface(GUI / Control Device)	Keypad, Mouse, PTZ Control, Remote Controller		
Archive File Format	EXE (Video Clip) / AVI (Video Clip) / JPEG (Still Image)		
NTP Server	Yes		
GMT Time Zone	Yes		
Auto DST	Yes		
Recording Qualities	Super / High / Standard / Low		
Recording Modes	Continuous / Alarm / Motion / Emergency		
Motion Detection	Yes (30 x 20)		
Playback Control	x1, x2, x4, x8, x16, x32, x64, Extreme		
PTZ Control	RS-485/422 Terminal Block, RS-485 through BNC		
Text Insertion (POS)	4		
Multi Language	English / Korean / Japanese / Czech / Dutch / Finnish / French / German / Italian / Polish / Portuguese / Russian / Spanish / Thai / Turkish / Vietnamese		
Central Monitoring Station	CMS Pro (Windows) / iCMS (Mac) / Web Client Pro		
Mobile Viewer	iPad / iPhone / Android		
Primary Storage	4 x SATA HDD, 1 x ODD		
Clip Copy Storage	1 Port		
eSATA	Built-in Internal DVD-RW, USB Memory Stick		
Dimension (WxHxD)	430 mm x 88 mm x 380 mm / 16.93 inch x 3.46 inch x 14.96 inch (Rack Type)		
Operating Temperature	5°C~40°C / 41°F~104°F		
Operating Humidity	0% ~ 90%		
Power Adapter	12V, 6A (72W)		

DIMENSION

* Design and specifications are subject to change without notice.



SYSTEM INTERCONNECTION

